

SEWER JETTING HOSE SERIES - SJC



Date Sheet - SJC7 Series

Part No.	I.D		O.D		Working Pressure		Burst Pressure		Min. Bend Radius		Weight	
	P/N	inch	mm	inch	mm	bar	psi	bar	psi	inch	mm	g/m
SJC7-08	1/2"	13.0	0.882	22.4	275	4,000	690	10,000	2.95	75	277	0.186
SJC7-10	5/8"	16.0	1.043	26.5	220	3,200	550	7,975	3.94	100	372	0.250
SJC7-12	3/4"	19.2	1.173	29.8	207	3,000	517	7,500	4.72	120	431	0.290
SJC7-16	1"	25.6	1.469	37.3	207	3,000	517	7,500	5.91	150	580	0.390
SJC7-20	1.1/4"	32.0	1.811	46.0	200	2,900	500	7,250	9.25	235	848	0.570
SJC7-24	1.1/2"	38.2	2.126	54.0	200	2,900	500	7,250	14.76	375	1,186	0.797



Date Sheet - SJC8 Series

Part No.	I.D		O.D		Working Pressure		Burst Pressure		Min. Bend Radius		Weight	
	P/N	inch	mm	inch	mm	bar	psi	bar	psi	inch	mm	g/m
SJC8-08	1/2"	13.0	0.882	22.4	345	5,000	862	12,500	3.94	100	292	0.196
SJC8-12	3/4"	19.2	1.173	29.8	250	3,625	625	9,060	4.72	120	460	0.309
SJC8-16	1"	25.6	1.469	37.3	250	3,625	625	9,060	5.91	150	643	0.432
SJC8-20	1.1/4"	32.0	1.811	46.0	250	3,625	625	9,060	9.25	235	985	0.662

Inner Core

Thermoplastic Compound

Reinforcement

Polyester aramid fiber braids

Cover

Anti-abrasion polyurethane

Application

Suitable for water applications in the pressure cleaning fields

Temperature

-40°C to +55°C (-40°F to +131°F)

Safety Ratio

1:2.5

